

## PATENT ABSTRACTS OF JAPAN

(11)Publication number : 05-060928

(43)Date of publication of application : 12.03.1993

(51)Int.Cl.

G02B 6/12

G02B 6/30

(21)Application number : 03-221853

(71)Applicant : NIPPON TELEGR &amp; TELEPH CORP &lt;NTT&gt;

(22)Date of filing : 02.09.1991

(72)Inventor : KONO KENJI  
YOSHIMOTO NAOTO  
KAMITOKU MASAKI

## (54) WAVEGUIDE TYPE SPOT SIZE CONVERTING ELEMENT

## (57)Abstract:

PURPOSE: To improve the conversion efficiency by using a multimode optical waveguide for spot size conversion and using the mode conversion effect and most suitably setting the length of the multimode optical waveguide.

CONSTITUTION: At least a first optical waveguide 3 where the spot size of guided light is small, a second optical waveguide 5 where the spot size of guided light is large, and an optical waveguide 4 for spot size conversion which connects these optical waveguides and converts the spot size are provided. In this case, width W and thickness D of a core 4 of the optical waveguide for spot size conversion are set to very large values. The multimode optical waveguide is used as the optical waveguide 4 for spot size conversion, and the length of the multimode optical waveguide 4 is so set that the spot size of guided light which is made incident from the first optical waveguide 3 and is propagated is expanded by the mode conversion effect in the multimode optical waveguide.

